

VT ElektroPlast VT Battery

ONE COMPANY - INFINITE POSSIBILITIES

DYNAMISM

PROGRESS

STABILITY

Test & Measuring Lab

HISTORY & OVERVIEW

- 2010 test lab was established based on increased demand of internal and external tests
- located in a separated building, in 140 m²
- belongs to the Central Quality Department
- provides every necessary public service: highpowered electricity, tap water, air-pressure system, air conditioner
- continuous support in automatized tester development at VTEP
- continuous improvement of test equipment, methods and processes
- most of the life-time testers were designed and built by VTEP engineers





HISTORY & OVERVIEW

We test products before and after they are launched to the markets; from design to mass production phase:

Test types:

- product design tests
- product release test
- battery tests in separated test lab
- product functionality-related tests
- product performance-related tests
- RoHS compliance
- approbation pre-tests
- internal tests for investigation of quality problems





HISTORY & OVERVIEW

- a technician performs the tests and he maintains the devices
- an engineer is responsible for leading the test lab and managing the activities
- contact with customers
- report the results of tests
- quick feedback to production if it is necessary

An internal SOP (Standard Operation Procedure) defines acts, roles and responsibilities of Test Laboratory.





TESTS – BATTERY TESTS

Description:

In the separated battery test lab we are able to execute battery cell and pack tests (even in fire protected climatic chamber):

- (abnormal) charging
- (forced) discharging
- capacity test
- short circuit analysis
- engineering / functional tests

We are able to measure and record during the test:

voltage, current impedance, temperature.

Beside these, we can do drop, as well.







TESTS – APPROBATION AND BATTERY TESTS

Equipment:

- programmable AC Power Source (Chroma 6530, Chroma 63113A)
- insulation/Current Leakage tester
 (GW Instek GPI-745A)
- digital power meter (Yokogawa WT210 + GPIB)
- digital multimeter (Picotest M3500A, Keysight 34461A)
- Hi-pot tester (Hioki 3561-01)
- force/torque meter (Mecmesin AFG 500)
- static torque wrench (Mecmesin TW15)
- contactless RPM meter







TESTS – CLIMATE TESTS

Our own programmable temperature and humidity chamber is suitable for climatic and ageing tests, especially for batteries, with fire protection system.

Specification:

model: ACS Discovery my DM600

volume: max 600L

temperature range: -40 / +180 °C

humidity range: 10 - 98% RH





TESTS – OTHER CLIMATE TESTS

Our own programmable temperature and humidity chamber is suitable for climatic and ageing tests

Specification:

model: WTH-L420

volume: 420L

temperature range: -20°C...+100°C

humidity range: 30%... 95% RH

total permitted load: 60 kg





TESTS – PORTABLE XRF FOR RoHS TESTS

- the XRF analyser helps to define concentrations of certain specific hazardous materials in electrical and electronic products in order to submit the products to RoHS regulations
- furthermore, it can help to define raw materials of samples, especially alloys
- the XRF technology is a quick and cheap way to analyse substances and filter hazardous materials

Features:

- model: NITON XL3t 700
- the first portable XRF tester by NITON





TESTS – KITCHEN PERFORMANCE TESTS

Kitchen appliances can be tested from an early phase of development or pre-serial phase and even in the mass production.

Features:

- extended foodstuff supply chain
- wide range of experience in kitchen tests
- pre-prepared raw material on the spot
- we can log and record the data of some tests with special hardwares and softwares





TESTS – APPROBATION AND BATTERY TESTS

Equipment:

- programmable AC Power Source (Chroma 6530, Chroma 63113A)
- insulation/Current Leakage tester
 (GW Instek GPI-745A)
- digital power meter (Yokogawa WT210 + GPIB)
- digital multimeter (Picotest M3500A, Keysight 34461A)
- Hi-pot tester (Hioki 3561-01)
- force/torque meter (Mecmesin AFG 500)
- static torque wrench (Mecmesin TW15)
- contactless RPM meter









TESTS – ENDURANCE TEST

Main qualities of different life-time testers:

- proper for skincare and personal care products; household appliances; cleaning centers
- working with pneumatic and air-pressure system
- one of testers works with circulating water
- parameters are adjustable manually or via software
- data are logged and recorded












TESTS – OTHER TESTS



fan test



abrasion test



drop test



electric strength test



CONFIDENTIALITY AND ACCESS CONTROL IN TEST LAB

- entrance is strictly controlled by access cards (all entry recorded)
- customer property, equipment and products are handled safely
- competitors' equipment are separated
- documents are stored electronically and protected from non-authorized access





MEASURING LABORATORY EQUIPMENT



GLOBAL PERFORMANCE CM MACHINE

Specification:

- model: GLOBAL Performance
- software: PCDMIS CAD ++
- measuring range: X: 700 Y: 700 Z: 500
- resolution: 0,001 mm
- measurement precision: MPE_E = from 1.5 + L/333 μm





OPTIV CLASSIC OPTICAL CM MACHINE

Specification:

model: HEXAGON OPTIV CLASSIC CMM

software: PCDMIS

measuring range: X: 300 Y: 200 Z: 200

resolution: 0,001 mm

measurement precision:

MPE (Exy): 2,8+L/150μmMPE (Ez): 5+L/150μm





KEYENCE IMAGE MEASUREMENT SYSTEM

Specification:

model: KEYENCE IM-7020

software: PCDMIS

measuring range: X: 200 Y: 200

resolution: 0,001 mm

measurement precision: ±(4 + 0,02 L) μm

sensor: 6,6 mega pixel





DEA GLOBAL COORDINATE MM

Specification:

model: DEA GLOBAL Performance

software: PCDMIS CAD ++

measuring range: X: 700 Y: 1000 Z: 500

resolution: 0,001 mm

measurement precision: ±5,5+0,009L(mm)µm





TESA VISIO 300 OPTICAL CM MACHINE

Specification:

model: TESA VISIO 300 OPTICAL CMM

software: PCDMIS

measuring range: X: 185 Y: 140 Z: 140

resolution: 0,001 mm

measurement precision: ±(2+0,006L(mm)µm)





TESA COORDINATE MEASUREMENT MACHINE

Specification:

model: TESA SA Micro-Hite

measuring range: X: 460 Y: 510 Z: 420

resolution: 0,001 mm

measurement precision: (3+4L/1000)µm





ATOS 3D SCANNER

As an example of the state-of-the-art technology, this device is able to create 3D model about any kind of object (sample part, tool insert etc.), which can be used for further measurement, analyses and reverse-engineering



Specification:

- model: ATOS Core 5M Professional Line
- software: Geomagic Design Direct
- measuring area: 185 x 140 mm
- working distance: 440 mm
- resolution: 0,01 mm
- measurement precision: ±2+0,006L(mm)µm^l







TINIUS OLSEN TENSILE TESTING MACHINE

Specification:

model: H20 K-W

measuring range: 20 kN

resolution: 0,3 N

measurement precision: >0,5%





IGV KV 02 HARDNESS MEASUREMENT MACHINE

Specification:

model: KV 02

measuring range: 0-70 HRC

measurement precision: <1 HRC





MITUTOYO DUROMETER

Specification:

model: Hardmatic HH331

measuring range: 0-100 Shore A

resolution: 1 Shore A

measurement precision: < ± 0,075 N





PORTABLE SURFACE ROUGHNESS GAUGE

Specification:

- model: TESA Rugosurf 10G
- measuring range: Ra:0-75 μm Rt:0,05-300 μm
- resolution: 0,001 μm
- measurement precision: 0,3 µm/25 mm





COLOR-GUIDE GLOSS METER

Specification:

- model: Gardner 6831
- measuring range: 400-700 nm L:0-100
- resolution: 0,01 GU
- measurement precision:
 - 0-10 GU=±0,2 GU
 - > 10 GU=±0,5 GU





INFRARED CAMERA

The device is proper to detect infrared energy. Temperature and heat distribution can be easily and precisely measured, therefore the heat-related problems can be evaluated.



Specification:

model: FLIR e50

thermal image quality: 240x180 pixel

thermal sensitivity: <0.05°C

temperature range: -20°C to +650°C





TÜV Rheinland



- extended contact with the Hungarian subsidiary
- thorough material investigation to detect RoHSbanned substances
- food-contact investigation
- continuous communication in approbationrelated topics (in product design phase)
- CE marking

Budapest University of



Technology and Economics

- industrial design, ergonomic studies
- functional and concept re-consideration of existing products
- (re)design human-machine interfaces
- 3D product visualizations and animations
- colour studies



Óbuda University



- the Central Research and Development
 Institute of Videoton has a cooperation with the
 Kálmán Kandó Faculty of Electrical
 Engineering of Óbuda University
- test of designed PCBs in EMC laboratory

Kaposvár University



- measurement of technological parameters physical properties
- alterations of the chemical composition near infrared spectroscopic (NIRS) and chemical analysis
- analysis of the effects exerted on the organoleptic traits
- cooperation within the dual education system



University of Pécs (PMMIK)



- cooperation within the dual education
 system at the faculty of mechanical and
 electrical engineering
- cooperation in R&D
- design and optimization of gear drive systems

Széchenyi István University, Győr



- cooperation since 2005
- the packaging laboratory of the institute is a professional partner in the release testing of automotive plastic parts and subassemblies



University of Dunaújváros



- full 3D injection molding simulation of products and mold optimization by using Moldex
 3D analysis software
- studies with different injection locations/types
- mold temperature uniformity check → cooling optimization
- optimization for moldability (reduced cycle time, optimal injection pressure); minimal part deformation; best visual part quality (minimal sink marks/welding lines)
- cooperation within the dual education system at the faculty of mechanical engineering (specialization of mechatronics)





THANK YOU FOR YOUR KIND ATTENTION!



VT ElektroPlast

VIDEOTON Elektro-PLAST Kft.

H-7400 Kaposvár 3 Izzó Str.

Phone: + 36 82 502 100 vtep@vtep.videoton.hu

Árpád Toldi

Quality Manager

Phone: + 36 82 502 328 Mobile: + 36 20 934 3084

toldi.arpad@vtep.videoton.hu

